

Linear rolling bearing

Field of the invention

The invention concerns a linear rolling bearing comprising a guide carriage with a U-shaped cross-section having a U-crossbar and two U-legs so that the guide carriage forms a carriage cavity and partially surrounds a guide rail while being slidably supported through balls on two longitudinal sides of the guide rail, each U-leg of the guide carriage having on an inner surface opposing the guide rail a ground raceway with an approximately quarter circle cross-section for the balls, the raceway being made by a grinding wheel whose diameter is larger than a diagonal dimension of the carriage cavity and whose axis of rotation is situated outside of the guide carriage and forms an acute angle with an axis of symmetry of the guide carriage.

Background of the invention

Raceways of carriages for profiled rail guides are made either using small vertical grinding wheels or several inclined grinding wheels arranged behind one another. Small grinding wheels result in unfavorable grinding values, short tool lives and poor surface quality. If several inclined wheels are used, the inner space of the guide carriage i.e., the carriage cavity likewise limits the size of the wheels. The advantage, however, is the inclined position of the grinding wheel. Therefore a limited but somewhat larger wheel is used.

At the same speed of rotation, a higher peripheral speed is obtained with a grinding wheel having a large diameter than with a wheel having a small diameter. With a large diameter, a higher grinding performance and a prolongation of the

service life of the wheel are obtained. The rotational speed of the grinding spindle cannot be infinitely increased because this would lead to a destruction of its bearings.

The publication EP 0 318 980 B1 discloses a linear ball bearing having a guide carriage, designated as a bearing body, that has a leg section with an upper groove with an approximately semi-circular cross-section for load-bearing balls and a lower groove with an approximately quarter circle cross-section for load-bearing balls. A drawback of this lies in the continuation of the radius of the upper groove up to the vertical inner wall of the leg section. This necessarily means that for making the upper groove by grinding, a small grinding wheel must be used.

The publication DE 33 31 287 C2 discloses a method of grinding the bearing body of a linear ball bearing. In this method, two raceways for load-bearing balls are ground on the inner surface of a U-crossbar of a guide carriage using a grinding wheel with a large diameter which is placed inclined to the guide carriage. The return canals for the balls that are arranged in circuits are configured as bores in the guide carriage and have to be made in special work steps in addition to the raceways for the load-bearing balls.

The publication DE 33 04 895 C2 shows a linear ball bearing with bearing bodies in which each ball recirculating shoe or bearing body comprises attached sheet metal parts viz., a W-shaped ball retainer for the load-bearing balls and a cover with a U-shaped cross-section which outwardly closes ball-guiding grooves for the non-loaded returning balls. Due to these additional sheet metal parts, the structure and assembly of the ball recirculating shoe is complicated and expensive.

The publication DE 30 19 131 A1 discloses a linear ball bearing in which continuous longitudinal openings are provided in the load-bearing regions and the return regions for the balls in the guide elements that are made as retaining plates. Therefore each guide element not only has in its ball region a narrow outwardly oriented opening but is also open towards the machine element that acts as a

guide carriage. The balls extend through these openings and are guided on longitudinal raceways that have to be made as grooves in the machine element so that additional machining and tool costs are incurred.

Objects of the invention

It is an object of the invention to provide a linear rolling bearing which can be made with low machining costs and a short machining time under good grinding conditions so that raceways with a very high surface quality can be realized.

This and other objects and advantages of the invention will become obvious from the following detailed description.

Summary of the invention

The invention achieves the above objects by the fact that a stop surface having a retaining contour for a guide member containing the balls is configured on a guide rail-distal outer surface of each U-leg of the guide carriage, and the raceway on one of the two U-legs and the stop surface having the retaining contour on the other of the two U-legs are made in common in one work step by the grinding wheel. Due to the simultaneous grinding of a raceway and a stop surface, the machining time of the guide carriage of the linear bearing is considerably shortened.

Further advantageous features of the invention and a detailed description of one example of embodiment of the invention shown in the drawings will be given hereinafter.

Brief description of the drawings

- Fig. 1 shows a linear bearing of the invention, partly in cross-section and partly in a front view;
- Fig. 2 shows a guide carriage of the linear bearing in cross-section, with a grinding wheel in contact with the surfaces to be ground.

Detailed description of the drawings

The linear rolling bearing illustrated in Fig. 1 comprises a guide carriage 1 that is supported through balls 3 on a guide rail 2 and is displaceable in the longitudinal direction of the rail. The linear rolling bearing is configured with two guide members 4 as a four-row bearing. Each guide member 4 contains two canals that effect the deflection and return of the balls 3 that are arranged in endless circuits. The guide carriage 1 has a U-shaped configuration and comprises a U-crossbar 5 and two U-legs 6 continuing therefrom. In this way, the guide carriage 1 forms a carriage cavity 7 and partially surrounds the guide rail 2 so that this projects into the carriage cavity 7.

Two raceways for balls 3 are configured on each longitudinal side of the guide rail 2 i.e., on each side of the guide rail 2 there is configured an upper raceway 8 and a lower raceway 9. These raceways 8 and 9 are parallel to each other in the longitudinal direction of the guide rail 2. The guide carriage 1 is supported on these raceways through the balls 3. For this purpose, the guide carriage 1 has on the inner surface of each U-leg 6 adjacent the guide rail 2, an upper raceway 10 that is situated nearer the U-crossbar 5 and a lower raceway 11 that is situated further away from the U-crossbar 5.

The load-bearing balls 3 are arranged on each longitudinal side of the guide rail 2 between each of the raceways 8 and 9 of the guide rail 2 and corresponding

raceways 10 and 11 of the guide carriage 1. Two of the four endless circuits of balls 3 are arranged on each longitudinal side of the guide rail 2. Each guide member 4 surrounds one of the U-legs 6 and is retained on a stop surface 12 of this U-leg 6. The stop surface 12 has a retaining contour and is situated on the guide rail-distal outer side of each U-leg 6. Two return canals for the balls i.e., an upper return canal 13 and a lower return canal 14, extending parallel to the raceways 10 and 11 of the U-leg 6 are formed in the guide member 4. At their ends, these canals merge into deflector canals that connect the return canals 13 and 14 to the associated regions of load-bearing balls 3 between the raceways 8 and 10, and between the raceways 9 and 11 respectively. Thus, the upper return canal 13 is connected to the raceway 10, and the lower return canal 14 is connected to the raceway 11.

The return canals 13 and 14 have an inner diameter corresponding to the diameter of the balls 3 and a radial opening 15 that extends in the longitudinal direction of the guide rail 2 and whose width is smaller than the ball diameter. On their longitudinal sides opposite the opening 15, the return canals 13 and 14 comprise a common bottom wall 16 so that the balls 3 are retained in their respective return canals 13 and 14 in the guide member 4 even when the guide member 4 is separated from the guide carriage 1. The guide member 4 can be made as an elastic component out of a plastic or a metal. Between its two raceways 10 and 11 for the load-bearing balls 3, the U-leg 6 comprises a projecting lug 17 that helps in unmistakably fixing and retaining the guide member 4 in the bearing.

Fig. 2 shows the manner in which the guide carriage 1 is machined with a grinding wheel 18. The axis of rotation 19 of the grinding wheel 18 is situated outside of the guide carriage 1 and is disposed at an acute angle α to the axis of symmetry 20 of the guide carriage 1. This permits a simultaneous grinding both of the raceway 10 situated nearer the U-crossbar 5 and the raceway 11 situated further away from the U-crossbar 5 on the inner surface of one of the U-legs 6 using one part of the grinding wheel 18 and, at the same time, a grinding of the stop surface 12 on the outer surface of the other U-leg 6 using another part of the grinding wheel 18. To

enable a part of the grinding wheel 18 to be inserted into the carriage cavity 7 and grind the raceways 10 and 11, both the raceways 11 of the guide carriage 1 situated further away from the U-crossbar 6 end at an imaginary connecting plane 21 that extends through the centers of the load-bearing balls 3 circulating on the raceways 11 and limits the two U-legs 6 on their undersides.

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000